



Acoustic Cavity Closer



The Product

John C Wilkins Acoustic Cavity Closer is a fire cavity and acoustic closer which can be used at separating floor and wall junctions. The Acoustic Cavity Closer provides acoustic insulation and fire resistance for 1 hour, by allowing the closure of the external wall cavity at the separating wall and floor junctions. The Cavity Closer is constructed from a semi-rigid mineral fibre insulation fully enclosed in a polythene bag.

The Facts

- Minimises sound transmission and the spread of fire
- Acoustic Cavity Closer meets Building Regulations Part E, where a separating wall or floor meets the external cavity wall, a mineral wool closer, which is protected by a suitable DPC must be used to minimise flanking sound
- Fire resistance material giving 1 hour Integrity and Insulation both vertically and horizontally

Specification

- **Length 1000mm**
- **Width 300mm**
- **Thickness 50, 65, 75 and 100mm**
- **Mineral wool material**

Installation

For expert installation, we offer our own installation service anywhere in the UK. Your installation will be performed to the highest standards by skilled and experienced tradesmen. These experts understand the importance of fitting acoustic materials absolutely perfectly and they have the specialist skills to ensure your John C Wilkins materials are fitted correctly every time. As they are both experienced and skilled, they are also able to provide a highly efficient and extremely cost-effective service.

**For further details, call John C Wilkins
Acoustic Installations on 01204 548400.**

APPLICATIONS

- Offices • Meeting Rooms • Hotels • Conference Centres
- Leisure Centres • Schools • Restaurants • Showrooms

JOHN C WILKINS ACOUSTIC SUPPLIES

Units 32-34, Waters Meeting Development,
Britannia Way, Bolton BL2 2HH
T: 01204 548400 F: 01204 366960